



Technical specifications

Klasik 2020 near field monitor

Type	Active – two power amplifiers – AB class
System	Two-way
Crossover Frequency	3.2 kHz
Dimensions: H x W x D	36 cm 21 cm 32 cm 14.2" 8.3" 12.6"
Free Field Frequency Response	± 2 dB: 39 Hz - 25 kHz
SPL max in 1m Free Field	RMS: 105.5 dB (single) Peak: 113.5 dB (pair)
Weight (piece)	10 kg / 22.1 lbs

Woofer	18 cm (7") cellulose, surround: rubber
Tweeter	1.9 cm (3/4") aluminium dome, surround: soft
Bass/Mid-Range Power Amplifier	100W RMS 8 Ω
Tweeter Power Amplifier	100W RMS 8 Ω
Total Harmonic Distortions	0.005 % 5W, 1 kHz; 0.1 % max 0.1 up to 50W, 20Hz up to 20kHz
Input Voltage Level for 96 dB SPL in Free Field @ 1m	0 dBu (i.e. 0.775 V) regulators in 0dB positions



Input Sensitivity Switch	-10.5dB, -9dB, -7.5dB, -6dB, -4.5dB, -3dB, -1.5dB, 0dB
Tweeter Level Switch	-1.5dB, 0dB, 1.5dB
Bass Controller Switch	Active - switch 1&3 Passive - switch 2
Ground-Lift Switch	On / Off
AC Voltage Switch	115 V or 230 V
Input	XLR (balanced), or RCA (unbalanced), 10 k Ω
Power Amplifiers Protections	Pop-free start & stop, thermal, short circuit, overload
Clipping	LED
Prevention from Interferences and Hums	GROUND-LIFT switch
Power Switching On	Lit up logo – blue LED
Woofer Amplifier Overdrive	Lit up logo – red LED