



Impulse Response Libraries

POWER AMPS

FRAME SNAKE EL34

Impulse response files created for and compatible with:

Acustica Audio's Nebula (Commercial Version)

Information Manual

Copyright © OwnHammer, LLC. All rights reserved.

Third Party Reference Disclaimer:

Any and all third party companies and products listed or otherwise mentioned in this document may be trademarks of their respective owners and are in no way affiliated or associated with OwnHammer, LLC. Product names are referenced solely for the purpose of identifying certain elements used in the equipment chain for impulse response capture, as well as related third party tools and applicable file loading platforms. Use of these names does not imply any cooperation or endorsement.

TABLE OF CONTENTS

Nebula Version Requirement	3
Installing the Program and Vector Files.....	3
Editing the Dictionary File.....	3
Programs Menu Location	3
Editing the Rate Conversion Value	4
General Guidelines	4
The Programs.....	4

NEBULA VERSION REQUIREMENT

Nebula format files are created with and intended for version 1.3.504 of Nebula 2 or 3 (commercial version only) and higher. These programs will not work with the Free or LE (such as Nebula CM, etc) derivatives. If using Nebula 2, it is a design of that platform to not display the text or slider value above the faders – this is a Nebula 3 value added feature and not related to the OwnHammer implementation.

INSTALLING THE PROGRAM AND VECTOR FILES

After extracting the zip-archive contents, to install the Programs, copy all of the .N2P files from:

```
..\OwnHammer for Nebula (Legacy)\Power Amps\Frame Snake EL34\Programs\
```

and paste them to:

```
..\[NEBULA INSTALL PATH]\Programs\
```

To install the Vectors, copy the .N2V files from:

```
..\OwnHammer for Nebula (Legacy)\Power Amps\Frame Snake EL34\Vectors\
```

and paste them to:

```
..\[NEBULA INSTALL PATH]\Vectors\
```

EDITING THE DICTIONARY FILE

After extracting the zip-archive content, look for the following file:

```
..\OwnHammer for Nebula (Legacy)\Power Amps\Frame Snake EL34\READ ME - Dictionary Tags.txt
```

Contained within this file are XML tags that can be added to the Rom.xml file located at:

```
..\[NEBULA INSTALL PATH]\Dictionaries\Rom.xml
```

XML files typically use character encoding that basic text editors are not capable of compiling. Editing and saving xml files in ASCII text encoding can break them, and is not recommended in most cases. For that reason, when editing xml files we use and recommend the Firstobject XML Editor found at http://www.firstobject.com/dn_editor.htm. This is a free, lightweight xml editor that refrains from implementing overcomplicated organizational schemes, therefore resembling a basic text editor and will auto detect the encoding of the Rom.xml and save it properly.

Altering the tag definitions will allow for functional menu browsing within the Nebula GUI, as it will allow the category descriptor to be presented in recognizable terms.

PROGRAMS MENU LOCATION

Once the files have been installed and the dictionary tags are populated properly, look for these programs to appear in the “OwnHammer (OWN)” > “Power Amps (PWR)” section of the pull down menu, which is populated by clicking on the large “Init” text near the top left corner of a freshly loaded Nebula instance.

EDITING THE RATE CONVERSION VALUE

This section primarily pertains to the pre-Nebula 4 version of Nebula 3. With the "Nebula 3 add-on for N4" version of the program, the RATECONVERSION tag values are set extremely high by default, and do not need adjusting.

If using these programs in sessions with sample rates other than 96 kHz, the RATECONVERSION tag will need to be edited in your plugin's xml parameter control file if you are experiencing strange audio behavior. This is easily identifiable as anything passing through the program will typically sound unnaturally dark and boxy. Editing the RATE CNV parameter on the MAST page of the plugin GUI is only a temporary fix, the following will ensure you will not need to repeat editing that value every time you use Nebula.

First, browse to wherever your Nebula2, Nebula2 Reverb, Nebula3, and/or Nebula3 Reverb plugins have been installed. Along with each of the above .dll files are .xml files. Using an XML EDITOR ONLY (such as the one mentioned in the previous section), open and edit each of the .xml files. In each will be a value most of the way down the file with the following tags:

```
<RATECONVERSION> 25000 </RATECONVERSION>
```

If you are having problems with the sound in DAW sessions other than 96 kHz, try increasing this number until the problem goes away. This number could fluctuate depending on your computer hardware and subsequent processing power. If the conversion is working properly, when you load a program you will see the following on the main program window:

```
FRT: 96000 -> 44100 Hz
```

If the value of the RATECONVERSION parameter is not high enough, in addition to bad sound this will read:

```
FRT: 96000 -> 96000 Hz <-
```

In this case, the <- at the end will be blinking. After adjusting this parameter you may also need to delete and re-add or reload Nebula instances in existing DAW sessions.

GENERAL GUIDELINES

As a general rule of thumb, be mindful of your levels making sure you never venture into the red. Being 10 kernels, you need to listen to the Power Amp programs for excessive breakup, cracks, pops, and garbling compression that can result from too much harmonic distortion. In the event you hear this you'll want to adjust:

- "Gain" fader (second to far right)
- Global input knob
- Kernel amount (fader value found on KRN tab)

Work first with the "Gain" fader. Moving this down is the quickest way to remove the sound. As you increase the input level value, you may also be required to lower this in tandem. Lowering the Kernel value will also help remove this, though you'll notice that the sound becomes more flat the less kernels present. This could be a good or a bad thing, but you have the option to control it nonetheless.

THE PROGRAMS

This Power Amp for Nebula contains the sampled power section of a Framus Cobra loaded with a quartet of EL34 tubes. The library includes 1 file pair containing 2 faders - Deep and Presence - just as on the amp.